

MORA EPOXY SEALER

Epoxy Primer and Surface Hardener.

Description:

MORA EPOXY SEALER: is a low viscosity, solvent containing, two component epoxy products.

Fields of Use:

- ✚ Surface hardener for concrete floors (2 coats).
- ✚ Primer for epoxy paints and joint sealants
- ✚ Strengthening plaster and concrete surfaces due to its high impregnation property.

Advantages:

- ✚ Designed as epoxy primer for various epoxy paint systems.
- ✚ High bond to cementitious and metallic surfaces.



Technical Data : (at 25° C)

Color	transparent 33 ± 1 %
Solid content (by weight) Density	100%
Mixing ratio, A: B by weight Pot life	1.8: 1
Initial setting time Final setting time Full hardness Recoating time	8 hours (decreases at higher temperatures) 2 hours
Rate of use	250 gm/m2

Directions for Use:

- ✚ The surface should be dry, clean and free of oils and grease.
- ✚ After thoroughly mixing of the 2 components of MORA EPOXY SEALER it can be applied by brush, rolling or spraying during pot life.
- ✚ If MORA EPOXY SEALER is processed in closed rooms, they should be sufficiently ventilated.
- ✚ Clean tools by MORA SOLVE 1.

Safety Precautions:

- ✚ Application should be carried out in well ventilated place.
- ✚ Gloves, protective clothing and eye goggles should be worn during application.
- ✚ Skin contaminations should be immediately cleaned with soap and plenty of water. Don't use solvent.
- ✚ If the material is splashed into the eyes, they should be immediately washed with water and then report to an eye specialist.
- ✚ Do not eat or smoke during application.

Storage:

2 years under suitable storage conditions and in closed containers.

Packages:



- ✚ Kits (A+B) 9.67 kg and 5.320 kg.
- ✚ Follow the mixing ratios- by weight - indicated on the package.

